

# AS-312

内置无源分频器驱动的两音路全频音箱

Built-in Passive Crossover Drive Two Full-range Speaker Sound

## 适用范围 Application

剧场、礼堂、多功能厅、KTV 房间、音乐酒吧等声音重放要求很高的场所  
High Standard Occasions Such As Mobile Performance, stadium, theater, lectur  
Ehall And Multi Functional Meeting Rooms

## 低音频段补强 Reinforcing Bass Frequencies


若需要延展低音频段,增强音乐感,可适配 AS-3115S 或 AS-3118S 超低频音箱  
If You Need To Extend The Bass Frequencies And Enhance The Sense Of Music,  
You Can Fit AS-3115S or AS-3118S SUBwoofer



AS-312

## 音箱技术参数 Technique specification

Drivers	单元组成	LF 低频:1x12" /3"Voice-coil ( Φ75mm 音圈 ) HF 高频:1x1" /1.75"Voice-coil ( Φ44mm 音圈 )
Frequency response	频率响应(-3dB)	50-18K Hz 赫兹
Dispersion ( HxV)	覆盖角度 ( -6dB)	80°x50°号角, 可 90°旋转 ( Rotatable Horn)
Sensitivity	灵敏度	97 分贝/1 瓦.1 米
Maximum SPL	最大声压级	122dB/AES 连续; 128dB/Peak 峰值
Nominal Impedance	标称阻抗	8 欧姆 ( OHMS)
Power handling	功率承受	300W(AES 额定)/600W ( 节目 )/1200W ( Peak 峰值)
Connectors	输入连接器	2xSpeakon NL4MP
Recommended AMP	推荐功放功率	450W - 600W @8Ω
Finish	表面处理	咖啡色环保耐磨油漆涂装 Environmentally Friendly Water- Based Wear-resistant Black Paint
Handing Position	吊装	内置多点螺丝承重吊挂和 1xΦ35mm 支撑座 Built-in Multi-point Screws Bearing Hang ing And 1xΦ35mm Support Base
Dimensions(HXWXD)	外形尺寸	600mmx(F377,R236)mmx400mm
Net Weight	净重	28.5kg



## 全频音箱系统 AS-SERIES

AS 系列优质驱动器适配倒相加载声学原理的箱体, 既有时尚的视觉感受, 也有完美的听觉内涵, 适用于 KTV 房间、音乐厅, 酒吧等扩声的场所。