

## AS-310P

内置无源分频器驱动的两音路全频音箱

Built-in Passive Crossover Drive Two Full-range Speaker Sound

### 适用范围 Application

剧场、礼堂、多功能厅、KTV 房间、音乐酒吧等声音重放要求很高的场所  
High Standard Occasions Such As Mobile Performance, stadium, theater, lectur  
Ehall And Multi Functional Meeting Rooms


### 低音频段补强 Reinforcing Bass Frequencies

若需要延展低音频段,增强音乐感,可适配 AS-3115S 或 AS-3118S 超低频音箱  
If You Need To Extend The Bass Frequencies And Enhance The Sense Of Music,  
You Can Fit AS-3115S or AS-3118S SUBwoofer




### 音箱技术参数 Technique specification


Drivers	单元组成	LF 低频:1x10" /2.5"Voice-coil ( 65mm 音圈 ) HF 高频:1x1" /1.75"Voice-coil ( 44mm 音圈 )
Frequency response	频率响应(-3dB)	55-18K Hz 赫兹
Dispersion ( HxV)	覆盖角度 ( -6dB)	90°x60°号角可 90°旋转 ( Rotatable Horn)
Sensitivity	灵敏度	95 分贝/1 瓦.1 米
Maximum SPL	最大声压级	119dB/AES 连续 ; 125dB/Peak 峰值
Nominal Impedance	标称阻抗	8 欧姆 ( OHMS)
Power handling	功率承受	250W(AES 额定)/1000W ( Peak 峰值)
Connectors	输入连接器	2xSpeakon NL4MP
Recommended AMP	推荐功放功率	375W - 500W @8Ω
Finish	表面处理	咖啡色环保耐磨油漆涂装 Environmentally Friendly Water- Based Wear-resistant Black Paint
Handing Position	吊装	内置多点螺丝承重吊挂和 1xΦ35mm 支撑座 Built-in Multi-point Screws Bearing Hang ing And 1xΦ35mm Support Base
Dimensions(HXWXD)	外形尺寸	500mmx(F323,R184)mmx325mm
Net Weight	净重	18kg




前视图/Front




侧视图/Side



背视图/Back



顶视图/Top



底视图/Bottom

### 全频音箱系统 AS-SERIES

AS 系列优质驱动器适配倒相加载声学原理的箱体, 既有时尚的视觉感受, 也有完美的听觉内涵, 适用于 KTV 房间、音乐厅、酒吧等扩声的场所。